HIGH COURT OF MADHYA PRADESH: JABALPUR

NOTICE INVITING e-TENDERS (NIT)

e-Tenders are invited for the "Installation of Local Area Networking work and other related work in the High Court of Madhya Pradesh and Subordinate Courts (District Courts and Tehsil Courts) in the State of Madhya Pradesh". The last date of online tender submission is 16th March, 2020 before 06:00 P.M. The sealed tender complete in all respect addressed to "Registrar General, High Court of Madhya Pradesh, Jabalpur" must be submitted before 05:00 P.M. on 17th March, 2020. The technical bids of the tender shall be opened on 18th March, 2020 at 11:00 A.M. The pre-bid meeting of tender is on 14th February, 2020 at 11:30 A.M. The detailed tender document is available in the official website of the High Court of Madhya Pradesh www.mphc.gov.in and Government e-procurement portal www.mptenders.gov.in.

Sd/REGISTRAR GENERAL

HIGH COURT OF MADHYA PRADESH: JABALPUR

NIT No.Reg(IT)(SA)/2020/201 Dated: 05-02-2020

Subject:- Installation of Local Area Networking and other related work in the High Court and Subordinate Courts in the State of Madhya Pradesh.

The Registrar General, on behalf of High Court of Madhya Pradesh invites online tenders for Installation of Local Area Networking work and other related work in the High Court of Madhya Pradesh and Subordinate Courts (District Courts and Tehsil Courts) in the State of Madhya Pradesh from Manufacturing Companies, reputed Bidders/Dealers, registered, bonafide, reputed, experienced and eligible firms who have executed similar nature of work in Court Premises/Government Ministries/Departments, Semi-government organizations including Public Sector Undertakings and reputed Private Organization with 05 years onsite support and warranty on all active and passive components and satisfying all other terms and conditions of the tender document.

S. No.	Estimated project cost	EMD (In Lakh Rupees)	Online Cost of Tender Document (in Rs.)	Last Date / Time of online tender Submission	Last Date/ Time of tender submission in hardcopy	Date and Time of Opening of Technical Bid (online/ hardcopy)	Time for Completion of the entire work / project
1.	2 Crore	4 Lakh	10,000/-	16 th March, 2020 before 06:00 PM	17 th March, 2020 before 05:00 PM	18 th March, 2020 at 11:00 AM	60 days

- Tender documents may be viewed or purchased online by interested and eligible bidders from the website www.mptenders.gov.in after paying Tender fee of Rs.10,000/-and Processing Fee, as applicable. The tender document is also available in website http://www.mphc.gov.in for reference.
- Bidders can submit its tender online at <u>www.mptenders.gov.in</u> on or before the key dates given above i.e. <u>16th March, 2020 before</u> <u>06:00 P.M.</u> The Physical copy of the Technical Bids also is to be submitted at the address below latest by <u>17th March, 2020 at 5:00</u> P.M.
- All further notifications/amendments, if any shall be posted on <u>www.mptenders.gov.in</u> and <u>www.mphc.gov.in</u> only. No separate communication shall be made with individual Bidders.
- The financial bids are to be submitted only online and no hard copy to be submitted along with the bid.

All other terms and conditions for submission of tender are contained in this document. If the date of submitting/opening of the Bid is declared as holiday then the bids shall be submitted / opened on next working day.

The Registrar General, High Court of Madhya Pradesh, Jabalpur (M.P.) reserves the right to accept or reject any or all bids without assigning any reason thereof.

Address for communication:-Registrar General, High Court of Madhya Pradesh, Jabalpur (M.P.).

Email:- mphc@nic.in Landline: 0761-2623358

1. <u>Instructions to the Tenderers /bidders:</u>

1.1 **DEFINITIONS:-**

- a) "The Employer" or "The Purchaser" means the "Registrar General, High Court of Madhya Pradesh, Jabalpur" and the "District Judge" of the District Courts.
- b) "The Bidder" means a firm or Joint Venture or Consortium which participates in the tender and submits its proposal.
- c) "Successful Bidder" means the Bidder, who, after the complete evaluation process, gets the Letter of Award. The Successful Bidder shall be deemed as "Contractor" appearing anywhere in the document.
- d) "The Letter of Award" means the issue of a signed letter by the Purchaser of its intention to award the work mentioning the total Contract Value. The timeline for delivery of products and services will start from the date of issue of Letter of Award.
- e) "The Contract" means the agreement entered into between the Employer and the Contractor, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.
- f) "The Contractor" means the individual or firm or OEM supplying the Goods / items and Services under this Contract.
- g) "The Contract Price" means the price payable to the Successful Bidder under the Letter of Award for the full and proper performance of its contractual obligations. The Contract Price shall be deemed as "Contract Value" appearing anywhere in the document.
- h) "Site Acceptance Test (SAT)" is a process of testing the contracted services provided by the Bidder at the locations specified by the Registrar General, High Court of Madhya Pradesh. SAT comprises of Product Acceptance Tests with respect to Technical Specifications and Bill of Materials as

specified in this tender, checking the installation, commissioning and integration of sub-components and integration with High Court software and acceptance of the Training at the site.

- i) "Services" means System Integration, Training and coordinating with the original equipment manufacturer (OEM) for installation, commissioning, system integration and maintenance for proper working of supplied equipments/items etc.
- j) "NIT" is the Notice Inviting Tender. It is essentially the Press Notification of the Tender.
- k) "**OEM**" means Original Equipment Manufacturer and/or Original Software Developer.
- This tender is subject to availability of funds / Budget from the State Government.
- 1.2 The technical bid of the tender shall be invited in sealed envelope consisting of EMD. The bid will be made and put in the sealed single envelope containing the title "Tender for Rate contract and Installation of Local Area Networking work in the High Court of Madhya Pradesh and Subordinate Courts (District Courts and Tehsil Courts) in the State of Madhya Pradesh" and addressed to "The Registrar General, High Court of Madhya Pradesh, Jabalpur" and the technical bid shall be submitted to the "Receipt /Inward Section of the High Court of M.P. before 05:00 P.M. on 17th March, 2020.

1.3 The financial bids are to be submitted online and no hard copy to be submitted along with the bid.

1.4 The date for the schedule of key events of this tender is given as under:-

SI. No.	Events	Date	
01.	Date of Pre-Bid meeting	14 th February, 2020 at 11:30 A.M. in the Conference Hall, South Block, High Court of Madhya Pradesh, Jabalpur.	
02.	Last date and time of online	16 th March, 2020 before 06:00 P.M.	

	tender submission.	
03.	Last date and time of hardcopy tender submission.	17 th March, 2020 before 05:00 P.M.
04.	Date and time of opening of technical bids.	18 th March, 2020 at 11:00 A.M.
05.	Date and time of opening of the price bids.	Date and time shall be communicated to all the qualified bidders.

All physical proposals have to be submitted ONLY in HARD BOUND (Hard bound implies such binding between two covers through stitching or otherwise whereby it may not be possible to replace any paper without disturbing the document) form with all pages sequentially numbered either at the top or at the bottom right corner of each page. It should also have an index giving page wise information of above documents. Incomplete proposal or those received without hard bound will summarily be rejected. All the Pages and Papers to be signed and sealed by the authorized signatory of the bidder.

2. Scope of Work:-

- i. The place of installation of Local Area Network and other related work will be the High Court of Madhya Pradesh and Subordinate Courts in the State of Madhya Pradesh.

 The rates for the LAN work shall be valid for the period of one year from the date of contract. The contract may be extended further for the period of one by the High Court looking to the satisfactory services of the vendor.
- ii. It will be duty of the bidder to have the credentials of the Service Engineers/Technical Persons deputed for installation of Local Area Network work to be duly verified and certified.
- iii. The bidder shall provide **Network Certified Engineer** to ensure proper maintenance and management of Local Area Networking work.
- iv. The bidder shall install network by laying the cables CAT-6 level as per specifications and terms of the tender.
- v. The bidder shall install network switches with uninterrupted power supply equipments and other peripherals necessary to make the network functional.
- vi. All the Network nodes shall be connected to Network Switches by appropriate casing covered cables.

- vii. All the hardware and the material used for installation of Local Area Networking shall be of good quality and of reputed make and brand as mentioned in the tender document.
- viii. It shall be the responsibility of the bidder to ensure connectivity of every Node with the Server installed in the Computer Room of the High Court / District Courts.
- ix. Each Network switch shall have sufficient provision of additional Nodes for future requirement.
- x. The bidder shall ensure that no damage is caused to the Building / Court premises and proper repairs and finishing is to be done after installation of the Network.

3. Section - III

3. Terms and Conditions for e-Tendering:-

- 3.1 For participation in e-tendering module, it is mandatory for prospective bidders registration website to get on www.mptenders.gov.in. Therefore, it is advised to all prospective bidders to get registration by making on line registration fees payment at the earliest.
- 3.2 Tender documents can be purchased *only online* on payment of tender fees and downloaded from website www.mptenders.gov.in by making online payment for the tender document fee.
- **3.3** Service and gateway charges shall be borne by the bidders.
- 3.4 Since the bidders are required to sign their bids online using class–III Digital Signature Certificate, they are advised to obtain the same at the earliest.
- 3.5 For further information regarding issue of Digital Signature Certificate, the bidders are requested to visit website www.mptenders.gov.in . Please note that it may take upto 7 to 10 working days for issue of Digital Signature Certificate. Department will not be responsible for delay in issue of Digital Signature Certificate.
- 3.6 If bidder is going first time for e-tendering, then it is obligatory on the part of bidder to fulfill all formalities such as registration, obtaining Digital Signature Certificate etc. well in advance.
- **3.7** Bidders are requested to visit our e-tendering website regularly for any clarification and / or due date extension.
- **3.8** Bidder must positively complete online e-tendering procedure at **www.mptenders.gov.in**
- **3.9** Department shall not be responsible in any way for delay /difficulties /inaccessibility of the downloading facility from the website for any reason whatever.
- **3.10** For any type of clarification bidders can / visit www.mptenders.gov.in. For any technical related queries please call at 24 x 7 Help Desk Number 0120-4001 002; 0120-4200 462; 0120-4001 005; 0120-6277 787; Technical support-eproc@nic.in. Support timings: Monday to Saturday from 10:00 AM to 7:00 PM.
- **3.11** Interested bidders may attend the free training programme in Bhopal at their own cost. For further query please contact help desk.
- 3.12 The bidder who so ever is submitting the tender by his Digital Signature Certificate shall invariably upload the scanned copy of the authority letter as well as submit the copy of same in physical form with the offer of particular tender.

The firms registered under NSIC are exempted for submission of tender fees and EMD. But they have to enclose valid documents in this regard.

4. Other terms and conditions:-

- i. The Bidder shall complete the installation of Local Area Network or other related work within <u>two month</u>, after the receipt of Work Order failing which the penalty of Rs 500/per day per work order shall be imposed.
- ii. The installation work shall be undertaken only by the Operator(s) duly authorized by the Registrar General to maintain the security of the High Court. The Bidder shall provide the list of technical persons in advance with their credentials to the Registrar General.
- iii. Tender document shall be available with the official website of the High Court i.e. www.mphc.gov.in and Government e-procurement portal www.mptenders.gov.in
- iv. The technical bid of the tender shall be opened in the High Court of Madhya Pradesh, Jabalpur on <u>due and time</u>. One authorized representative of the bidder may remain present at the time of opening of the bids. Tender will be finalized after considering the proposals. All tenderers or any of the tenderer may be called for further negotiations before considering his/their proposal.
- v. The Registrar General shall have the absolute right to select/reject any tender for installation of Network on the basis of rate, quality and services proposed in the tender.
- vi. The bidder is required to submit <u>brochure(s) of the Hardware items that is proposed to be supplied and installed for Local Area Network and other related work.</u>
- vii. The Registrar General has the right of accepting or rejecting any or all tenders without specifying any reason(s) thereof. The Registrar General is under no obligation to accept the lowest tender.
- viii. There is no obligation on the part of the Registrar General to inform the unsuccessful Tenderer of the outcome of the Tender process and reasons for rejection of the tender.
- ix. The successful bidder shall forthwith engage/depute qualified Service Engineers/Operators to install the Local Area Network in the High Court of Madhya Pradesh and Subordinate Courts in the State of Madhya Pradesh.

- x. In case of pecuniary loss suffered by any of the users/beneficiaries of the High Court of Madhya Pradesh or Subordinate Courts attributed to the Contractor, the Registrar General will have the right to forfeit the Security Deposit and in case the Security Deposit falls short to match the pecuniary loss being insufficient, such balance will be recovered from the payments due to the Contractor.
- xi. Rates offered in the tender will not be enhanced after acceptance of the Tender. No upward revision will be allowed under any circumstances whatsoever.
- xii. Under no circumstances, shall the bidder appoint any sub-contractor or sub-lease the contract. If it is found that the contractor has violated these conditions, the contract will be terminated forthwith without any notice, by the authority who has approved the award of the contract.
- xiii. The successful tenderer will be required to furnish security deposit of 10% of the work order value within 15 days from the date of issue of Work Order. The security deposit shall be in the form of FDR through any nationalized bank in favour of Registrar General or unconditional Bank Guarantee of any Nationalized Bank of equal amount. The security deposit money will be refundable only after successful installation of Local Area Network. The security deposit will be forfeited if during the period of installation services of the bidder are found to be unsatisfactory in any respect.
- xiv. The work order can be terminated by the Registrar General at any point of time without assigning any reason if the work of the contractor is found unsatisfactory. In this respect, the decision of the Registrar General will be final and binding on the contractor. The Registrar General reserves the right to accept or reject any bid in whole or in part without assigning any reasons thereof.
- xv. The bills in triplicate for the work completed on the basis of approved rates shall have to be submitted in favour of the Registrar General / District and Sessions Judge, Jabalpur for effecting payment. No advance payment shall be made for the Job/Work done.
- xvi. The bidder shall submit the report of successful installation of Local Area Network or other Network related work, which shall be verified by the Officers

nominated by the Registrar General after checking connectivity of every Node with the Server / Network Switch. With regard to successful installation of local area network, the decision of Registrar General shall be final and binding.

- xvii. The job carried out shall be to the satisfaction of the Registrar General after getting certification from the In-Charge, Computer Section of the District Courts failing which deductions upto 10% of the total bill shall be made. Depending upon the severity of negligence, the Registrar General reserves the right to blacklist the agency for a suitable period or from further participation in any of the jobs to be done for the High Court of Madhya Pradesh, Jabalpur. The decision of the Registrar General shall be final and binding on the Firm.
- xviii. Premature withdrawal of the tender by the tenderer shall make him liable for forfeiture of the earnest money deposit.
- xix. All the pages of the tender document should be serially numbered and duly stamped and signed by the bidder.
- xx. The Registrar General reserves the right to review the performance whenever so desires, and also to terminate the Work Order at any point of time during the installation in case the performance and the service rendered by the Bidder is found to be unsatisfactory. The decision of the Registrar General shall be binding on the Bidder. The Word Order can also be terminated at any point of time if the above mentioned work is no more required.
- xxi. The Registrar General reserves the right to vary, amend or alter any terms and conditions of the Tender Document at the time of placement of work order and before executing the contract.

5. Eligibility Criteria :-

i. The Agency / Firm applying should possess valid Income Tax PAN No., GST registration No. The Agency should have a minimum experience of 05 years in Local Area Networking installation work at Government Organization, Public Sector Companies and other reputed Private Organizations.

- ii. Copies of the following documents should be submitted along with the Bid.
 - a. GST registration
 - b. Latest GST return of the Company.
 - c. Income Tax PAN card.
 - d. Income Tax Return for the last three years i.e. 2016-17, 2017-18 and 2018-19.
 - e. Valid ISO / ISI Certificate of the products to be installed.
 - f. Documents showing the experience of Five years in providing similar work i.e. Local Area Networking work.
 - The online **Earnest Money Deposit (EMD) of** g. Rs.4,00,000/-(Rupees Four Lakh Only) through Demand Draft/Pav Order/ unconditional Bank Guarantee drawn in favor of Registrar General, High Court of Madhya Pradesh, Jabalpur. The Government organizations are exempted for submission of EMD.
 - h. Non-refundable <u>online tender fees of</u>
 <u>Rs.10,000/-</u> (Rupees Ten Thousand only)
 drawn in favor of Registrar General, High
 Court of Madhya Pradesh. The Government
 organizations are exempted for submission of
 EMD.
 - i. List of existing LAN installations being maintained as per details following:
 - Name of the Company/Type of LAN being maintained/No. of nodes/Last year's turn over.
 - j. Escalation matrix for lodging the complaint during the execution of warranty period.
 - k. High Court/Subordinate Courts should be able to log the call with the OEM directly online/offline for the active component. Support should be provided by the OEM directly onsite for the

- replacement of active component for the period of 5 years.
- I. Brochures of the product with detailed specifications and MAF.
- m. The valid ISO 9001 certificate of the bidder in the field of LAN and other Network work. The Government Organization are exempted for submission of ISO certificate of the organization as per the tender document.
- n. The *Annual* average turnover during last three financial years to be at least **Rupees 02 crore**.

6. Evaluation of Bids:

- 6.1 The Techno-Commercial Bid and price Bid will be evaluated as a package simultaneously. It must satisfy all the terms and conditions mentioned in this document and must be accompanied by all the requisite documents.
- **6.2** Filling up of all the columns in Techno-Commercial Bid and Price Bid is compulsory.

7. Earnest Money Deposit:

The proposal should be submitted along with **online** application fee of Rs.10,000/- (Rs. Ten Thousand only) and Earnest Money Deposit (EMD) of Rs.4,00,000/- (Rs. Four Lakh only) in the form of a demand draft / pay order / FDR / unconditional Bank Guarantee drawn in favour of "Registrar General, High Court of Madhya Pradesh, Jabalpur" of any Nationalized / Scheduled bank payable at Jabalpur. The Bid submitted without EMD and/or the application fee shall be summarily rejected. The earnest money will be returned to all the unsuccessful Tenderer after finalization of the Tender. No interest shall be paid on the Earnest Money Deposit for delay in return for any reason, whatsoever may be.

8 SPECIFICATIONS:-

8.1: Items with details (Bill of material)

S.No.	Item Description	OEM Make/Part No.	Proposed make/brand by the bidder	Technically Complied Yes/No (to be filled by bidder)	Category
	UTP CAT 6	D-link/ Legrand			
1.	cable (Box of	/Molex or equivalent			Α
	305 m)	brand of repute			
	24 port Patch	D-link/ Legrand/			
2.	Panel CAT 6	Molex or equivalent			Α
	(each)	brand of repute			
3.		utlet CAT 6 (facepla			
<u> </u>	complete set) D)-link/ Legrand/Molex	or equivalent	brand of repu	te
0	4	D-link/ Legrand/			
3 a	1-port	Molex or equivalent			Α
		brand of repute			
0.1	0	D-link/ Legrand/			
3 b	2-port	Molex or equivalent			Α
		brand of repute			
2.0	1 22 24	D-link/Legrand/			
3 c	4-port	Molex or equivalent			Α
	Datab Carda	brand of repute CAT 6 (each) At le	ost in 2 sol	OUR OS BOR	ordor) D
4.		olex or equivalent bra		oui as pei	order) D-
	mind Ecgrana/in	D-link/Legrand/			
4 a	1 Meter	Molex or equivalent			Α
	1 Wicker	brand of repute			
		D-link/Legrand/			
4 b	2 Meter	Molex or equivalent			Α
		brand of repute			
	FIBER COMPO	NENTS- Fiber Optic	indoor/outdo	or tight buffe	red cable
5.		M) (Per Meter) 3M/ fin			
	equivalent bran	d of repute	-	•	
		3M/ finolex /Fujitsu/			
5 a	6 coro	D-link/Legrand/			^
За	6 core	Molex or equivalent			Α
		brand of repute			
		3M/ finolex /Fujitsu/			
5 b	12 core	D-link/Legrand/			Α
3.0	12 0016	Molex or equivalent			^
		brand of repute			
6.		tdoor armoured cabl [/] D-link/Legrand/Mole			
		3M/ finolex /Fujitsu/			
6 a	6 core	D-link/Legrand/			Α
Ua	0 0016	Molexor equivalent			^
		brand of repute			
		3M/ finolex /Fujitsu/			Α
6 b	12 core	D-link/Legrand/			^
		Molex			
7.		connector SC Type, E Molex or equivalent b			x /Fujitsu/
		3M/ finolex /Fujitsu/			
7 a	SM	D-link/Legrand/			Α
ra	OIVI	Molex or equivalent			^
		brand of repute			

8.		onnectors LC Type, I Molex or equivalent b			ex /Fujitsu/
8 a	SM	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute			A
9.		oigtail SC Type, 1 n olex or equivalent bra		3M/ finolex /	Fujitsu/ D-
9 a	SM	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute			A
10.		oigtail LC Type, 1 molex or equivalent bra		3M/ finolex /	Fujitsu/ D-
10 a	SM	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute			A
11.	· -	Patch Cord, MM SC to blex or equivalent bra	•	3M/ finolex /	Fujitsu/ D-
11 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute			A
12.		Patch Cord, MM, SC plex or equivalent bra		3M/ finolex /	Fujitsu/ D-
12 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute	·		A
13.	Optical Fiber Patch Cord, SM, SC to LC (each) 3M/ finolex /Fujitsu/ D-link/Legrand/Molex or equivalent brand of repute.				
13 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute			A
14.		Patch Cord, SM, SC of olex or equivalent bra			Fujitsu/ D-
14 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute			A
15.	_	Patch Cord, SM, LC to blex or equivalent bra	• •		Fujitsu/ D-
15 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute			A
16.		atch Cord, MM, OM-3 Molex or equivalent b			ex /Fujitsu/
16 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute			Α
17.		all mount enclosure, ies (each) 3M/ finol			
17 a	LIU WITH SC MM COUPLER	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex			A
17 b	LIU WITH SC	3M/ finolex /Fujitsu/			Α

17 c LIU WITH LC D-MM COUPLER Mobre 17 d LIU WITH LC D-SM COUPLER Mobre 18. LIU, 12 fiber, 1U/ 2 SC/LC couplers link/Legrand/Molex 18 a LIU WITH SC MM COUPLER Mobre 18 b LIU WITH SC D-MM COUPLER Mobre 30 D-MM COUPLER Mobre 31 D-MM COUPLER Mobre 31 D-MM COUPLER Mobre 32 D-MM COUPLER Mobre 33 D-MM COUPLER Mobre 34 D-MM COUPLER Mobre 35 D-MM COUPLER Mobre 36 D-MM COUPLER Mobre 37 D-MM COUPLER Mobre 38 D-MM COUPLER MOBRE		mount enclosure & fitted wh) 3M/ finolex /Fujitsu/pute
17 c LIU WITH LC MM COUPLER MG brack	// finolex /Fujitsu/ link/Legrand/ plex or equivalent and of repute // finolex /Fujitsu/ link/Legrand/ plex or equivalent and of repute U drawer style 19 " Rack or equivalent brand of re & all accessories (eack or equivalent brand of re // finolex /Fujitsu/ blex or equivalent plex or equivalent and of repute	mount enclosure & fitted wh) 3M/ finolex /Fujitsu/
17 c LIU WITH LC MM COUPLER MG brack SM COUPLER MG brack SM COUPLER MG brack SC/LC couplers link/Legrand/Molex MM COUPLER MG brack SM COUPLER MG brack SM COUPLER MG brack SM COUPLER MG SM COUPLER MG brack S	link/Legrand/ plex or equivalent and of repute // finolex /Fujitsu/ link/Legrand/ plex or equivalent and of repute U drawer style 19 " Rack of all accessories (eack or equivalent brand of re // finolex /Fujitsu/ link/Legrand/ plex or equivalent and of repute	mount enclosure & fitted wh) 3M/ finolex /Fujitsu/
17 c MM COUPLER Me bra 3N SM COUPLER Me bra 3N SM COUPLER Me bra 3N SM COUPLER Me bra 3N SC/LC couplers link/Legrand/Molex MM COUPLER Me bra 3N SM COUPLER Me bra 3N SM COUPLER ME SM CO	blex or equivalent and of repute // finolex /Fujitsu/ link/Legrand/ blex or equivalent and of repute U drawer style 19 " Rack of all accessories (eack or equivalent brand of re // finolex /Fujitsu/ blex or equivalent and of repute	mount enclosure & fitted wh) 3M/ finolex /Fujitsu/
17 d LIU WITH LC SM COUPLER Mobra 18. LIU, 12 fiber, 1U/ 2 SC/LC couplers link/Legrand/Molex 18 a LIU WITH SC MM COUPLER Mobra 18 b LIU WITH SC D- MM COUPLER Mobra 3N D- LIU WITH SC D- MM COUPLER MOBRA 3N D-	and of repute // finolex /Fujitsu/ link/Legrand/ blex or equivalent and of repute U drawer style 19 " Rack of all accessories (eack or equivalent brand of re // finolex /Fujitsu/ link/Legrand/ blex or equivalent and of repute	mount enclosure & fitted w h) 3M/ finolex /Fujitsu/ pute
17 d LIU WITH LC SM COUPLER Mobre 18. LIU, 12 fiber, 1U/ 2 SC/LC couplers link/Legrand/Molex 18 a LIU WITH SC MM COUPLER Mobre 18 b LIU WITH SC D- MM COUPLER Mobre 30 D- 31 D-	// finolex /Fujitsu/ link/Legrand/ blex or equivalent and of repute U drawer style 19 " Rack & all accessories (eack or equivalent brand of re // finolex /Fujitsu/ blex or equivalent and of repute	mount enclosure & fitted w h) 3M/ finolex /Fujitsu/ pute
17 d LIU WITH LC SM COUPLER Mobre 18. LIU, 12 fiber, 1U/ 2 SC/LC couplers link/Legrand/Molex 18 a LIU WITH SC MM COUPLER Mobre 18 b LIU WITH SC D- 30 D- 31 D-	link/Legrand/ plex or equivalent and of repute U drawer style 19 " Rack & all accessories (eac a or equivalent brand of re // finolex /Fujitsu/ plex or equivalent and of repute	mount enclosure & fitted w h) 3M/ finolex /Fujitsu/ pute
SM COUPLER Mobra 18. LIU, 12 fiber, 1U/ 2 SC/LC couplers link/Legrand/Molex 18 a LIU WITH SC MM COUPLER Mobra 18 b LIU WITH SC D- MM COUPLER Mobra 3N 18 b LIU WITH SC D-	blex or equivalent and of repute U drawer style 19 " Rack to the style and accessories (eact or equivalent brand of reful to the style and of repute to the	mount enclosure & fitted w h) 3M/ finolex /Fujitsu/ pute
18. LIU, 12 fiber, 1U/ 2 SC/LC couplers link/Legrand/Molex 18 a LIU WITH SC MM COUPLER Mobre 18 b LIU WITH SC D- 30 D- 31 D-	and of repute U drawer style 19 " Rack of the style and of recessories (eact or equivalent brand of recessories // finolex /Fujitsu/blex or equivalent and of repute	h) 3M/ finolex /Fujitsu/ pute
18. SC/LC couplers link/Legrand/Molex 18 a LIU WITH SC D-MM COUPLER Mobre 3N bridger 18 b LIU WITH SC D- 3N COUPLER D- 3N D	& all accessories (eac c or equivalent brand of re d/ finolex /Fujitsu/ link/Legrand/ blex or equivalent and of repute	h) 3M/ finolex /Fujitsu/ pute
18 a LIU WITH SC MM COUPLER MM br. LIU WITH SC D- MM COUPLER MM br. 3N LIU WITH SC D-	or equivalent brand of re // finolex /Fujitsu/ link/Legrand/ blex or equivalent and of repute	pute
18 a LIU WITH SC D-MM COUPLER MG br.	// finolex /Fujitsu/ link/Legrand/ blex or equivalent and of repute	
18 a LIU WITH SC MM COUPLER MM br. 3M	link/Legrand/ blex or equivalent and of repute	Α
MM COUPLER Me brack brac	plex or equivalent and of repute	Α
branch	and of repute	
LIU WITH SC D-		
LIU WITH SC D-	ii iiiloick /i ujitou/	
	link/Legrand/	
	olex or equivalent	Α
	and of repute	
31/	// finolex /Fujitsu/	
	link/Legrand/	A
MM COUPLER Me	olex or equivalent	
· · · · · · · · · · · · · · · · · · ·	and of repute	
	•	
1 1 2 7 1		Α
	<u>-</u>	
Installation & Torn		Site Certification of UTP a
19. Fiber Cabling	•	
In-building		
1		
10 		1
	s per actual	Α
6 Cable (Per	s per actual	Α
6 Cable (Per Meter)		A
6 Cable (Per Meter) Installation & As	s per actual	A
6 Cable (Per Meter)		A
6 Cable (Per Meter) Installation & As Termination or Information		
6 Cable (Per Meter) Installation & As Termination or Information outlets (including		A
6 Cable (Per Meter) Installation & As Termination or Information outlets (including termination of		
6 Cable (Per Meter) Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A		
6 Cable (Per Meter) Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O	per actual	
19 b Cable (Per Meter) Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & As		
6 Cable (Per Meter) Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & As Termination of	per actual	
6 Cable (Per Meter) Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & As	per actual	
6 Cable (Per Meter) Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & As Termination of UTP Cables on	per actual	A
19 b 19 b Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & Termination of UTP Cables on Patch Panel CAT 6/ CAT 6A with wire	per actual	A
6 Cable (Per Meter) Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & Termination of UTP Cables on Patch Panel CAT 6/ CAT 6A with wire manager	per actual	A
6 Cable (Per Meter) Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & Termination of UTP Cables on Patch Panel CAT 6/ CAT 6A with wire manager Performance As	per actual	A
6 Cable (Per Meter) Installation & As Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & Termination of UTP Cables on Patch Panel CAT 6/ CAT 6A with wire manager Performance testing of the	per actual	A
19 b Installation & As Termination or Information outlets (including termination of CAT 6A Cable on I/O Installation & Termination of UTP Cables on Patch Panel CAT 6/ CAT 6A with wire manager Performance testing of the laid UTP CAT 6/ CAT 6 A	per actual	A
6 Cable (Per Meter) Installation & Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & Termination of UTP Cables on Patch Panel CAT 6/ CAT 6A with wire manager Performance testing of the laid UTP CAT 6/ CAT 6 A	per actual	A
6 Cable (Per Meter) Installation & Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & Termination of UTP Cables on Patch Panel CAT 6/ CAT 6A with wire manager Performance testing of the laid UTP CAT 6/ CAT 6 A (Penta Scanner)	per actual	A
6 Cable (Per Meter) Installation & Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O Installation & Termination of UTP Cables on Patch Panel CAT 6/ CAT 6A with wire manager Performance testing of the laid UTP CAT 6/ CAT 6 A	per actual	A
18 d LIU WITH LC SM COUPLER Mo bro 19. Installation & Term Fiber Cabling In-building laying of UTP	I/ finolex /Fujitsu/ link/Legrand/ olex or equivalent and of repute ination, Documentation &	A Site Certification of UTP

20.		on for UTP CAT6/CA arranty (Per site) As p	T 6A & Fiber cabling with per actual.	15 years
20 a	Site up to 100 Nodes (Per site)	As per actual		Α
20 b	Site up to 500 Nodes (Per site)	As per actual		Α
21.	Supply & fixing (OEM)	of ISI/ISO marked P	VC duct of Size (Per Meter)	ISI / ISO
21 a	15 x 15 mm	ISI / ISO (OEM)		Α
21 b	30 x 25 mm	ISI / ISO (OEM)		Α
21 c	40 x 25 mm	ISI / ISO (OEM)		Α
22.	Supply and fixir	ng of PVC Conduit of	OD Size (Per Meter) ISI / ISC	O (OEM)
22 a	20 mm	ISI / ISO (OEM)		Α
22 b	32 mm	ISI / ISO (OEM)		Α
22 c	40 mm	ISI / ISO (OEM)		Α
23.	Removal of Old UTP/ Fiber / coaxial RS 232/telephone cables (per Meter) In building			A
24.	laying of fiber in duct/ conduit (per meter)			A
25.		of fiber cable (per Me	ter)	
25 a	Excavation and resurfacing of the Soft soil (depth 1 meter)			A
25 b	Excavation and resurfacing of the concreter (depth 1 meter)			Α
25 c	Overhead or through pole			Α
26.	Supply and Installation / Fixing of 2" (Inches) diameter HDPE PVC Jacket Underground or on surface (Per Meter)			Α
27.	SC/LC connector termination on fiber optic cable			A
28.	Fusion/ Mechanical splicing			Α
29.	Supply and installation of buffer tubing kit			

	Performance testing of laid fiber Optic cable for continuity length & DB			_
30.	loss as per EIA/TIA - 455- 60 document for FO test procedures & documentation of the results.			A
31.		mounting Racks	1	<u> </u>
31 a	19" Rack, wall Mount 530 mm depth, 9 U Height, (lockable) with all accessories(At	Rittal/D-link,Valrack or equivalent brand of repute		A
	least 2 cooling fan,1 cable manager, 15A 6port spike guard)			
31 b	19" Rack, wall Mount 530 mm depth, 12 U Height, (lockable) with all accessories	Rittal/D-link,Valrack or equivalent brand of repute		Α
31 c	19" Rack, wall Mount 800 mm depth, 24 U Height, (lockable) with all accessories(At least 2 cooling fan,1 cable manager, 15A 6port spike guard)	Rittal/D-link,Valrack or equivalent brand of repute		A
31 d	19" Rack, wall Mount 1000 mm depth, 32 U Height, (lockable) with all accessories (At least 2 cooling fan,1 cable manager, 15A 6port spike guard)	Rittal/D-link,Valrack or equivalent brand of repute		A
31 e	19" Rack, wall Mount 1000 mm depth, 42 U Height, (lockable) with all accessories (Atleast 2 cooling fan,1	Rittal/D-link,Valrack or equivalent brand of repute		Α

	aabla managar			
	cable manager,			
	15A 6port spike guard)			
	· ·			
32.		Oocument Preparation)	
	for up to 100			_
32 a	network nodes,			Α
	per node			
	for up to 500			
32 b	network nodes,			Α
	per node			
	8 port Network			
	Switches	CISCO / Dell / HP /		_
33.	(manageable)	Juniper		Α
	Specification-	Cump Ci		
	"A".			
	12 port			
0.4	Aggregation	CISCO / Dell / HP /		
34.	Switch	Juniper		Α
	Specification-	'		
	"B".	01000 / D = 11 / L ID /		
	24 port	CISCO / Dell / HP /		
25	Aggregation	Juniper		A
35.	Switch			Α
	Specification- "C".			
	24 port			
	Ethernet			
	managed			
	enterprise			
	series switch			
	with all	CISCO / Dell / HP /		
36.	accessories	Juniper		Α
	and Power	Campon		
	over Ethernet			
	(PoE)			
	Specification-			
	"D".			
	24 port			
	Ethernet			
	managed			
	enterprise	CISCO / Dell / HP /		
37.	series switch	Juniper		Α
	with all	Julipel		
	accessories.			
	(Specification-			
	"E".)			
	24 port			
	Ethernet			
	managed			
	enterprise	CISCO / Dell / HP /		_
38.	series switch	Juniper		Α
	with all	- 2		
	accessories.			
	(Specification-			
	"F".) 24 port			
	24 port Ethernet			
39.	managed enterprise	CISCO / Dell / HP /		Α
J.	series switch	Juniper		^
	with all			
	accessories.			
	40003301163.	l		

	(Specification- "G".)			
40.	Dual Band Mesh WiFi router,2 number of gigabit Ethernet ports, should be expandable with smart roaming feature	D-link/ CISCO / Netgear/Linksys/Dell / HP / Juniper		A
41.	*SFP modules of SM Should support both SM and MM fiber at minimum 1 GBPS. Should be same OEM as item no. 34 to 39	CISCO / Dell / HP / Juniper		A
42.	Media convertor SM (Should support 10/100/1000 Ethernet to 10/100/1000 fiber Onsite support)	Reputed make		A
43.	Media convertor MM (Should support 10/100/1000 Ethernet to 10/100/1000 fiber Onsite support).	Reputed make		A
44.	Stacking module with stacking cable. Should be same OEM as item no. 34 to 39			A
45.	10G SFP module (should support single or multi mode) should be same OEM as item no. 34 to 39			A
	40G SFP		 	
46.	module (single mode) should be same OEM as item no. 34 to 39			A

	module (multi mode) should be same OEM as item no. 34 to 39				
48.	UTP CAT 6A cable (Box of 305 m)	D-link/ Legrand/Molex or equivalent brand of repute			A
49.	Patch Cords CAT 6A (each) at least in 2 colour as per order) D-link/ Legrand /Molex or equivalent brand of repute				
49 a	3 Meter	D- link/Legrand/Molex or equivalent brand of repute			A
49 b	7 Meter	D- link/Legrand/Molex or equivalent brand of repute			A
49 c	10 Meter	D- link/Legrand/Molex or equivalent brand of repute			A

SPECIFICATIONS :- Part - "B"

8.1: Items with details (Bill of material)

S.No.	Item Description	OEM Make/Part No.	Proposed make/brand by the bidder	Technically Complied Yes/No (to be filled by bidder)	Category
1.	Patch Cord order/require	, ,	At least	in 2 colour	as per
1 a	5 Meter	D- link/Legrand/Molex or equivalent brand of repute			В
2.		r Connector SC T nk/Legrand/Molex or			
2 a	ММ	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute			В
3.		r Connectors LC			
	/rujitsu/ D-III	nk/Legrand/Molex or 3M/ finolex	equivalent bi	and of repute	<u>;</u>
3 a	MM	/Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute			В
4.	_	r pigtail SC Type, 1 /Molex or equivalent	• •		Fujitsu/ D-
4 a	ММ	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute			В
5.		r pigtail LC Type, 1 /Molex or equivalent			Fujitsu/ D-
5 a	MM	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute	•		В
6.		Patch Cord, MM SO			Fujitsu/ D-
6 a	10 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute			В
6 b	20 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute			В
7.	for old netwo	r Patch Cord, SM, S orks (at the time of r su/ D-link/Legrand/N	naintenance v	work as per te	nder). 3M/
7 a	3 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent			В

		brand of repute			
		3M/ finolex			
		/Fujitsu/ D-			
7 b	10 meters	link/Legrand/Molex			В
'	10 11101010	or equivalent			
		brand of repute			
		3M/ finolex			
		/Fujitsu/ D-			
7 c	20 meters	link/Legrand/Molex			В
' 0	20 11101013	or equivalent			
		brand of repute			
	Ontical Fibe	er Patch Cord, MM, S	C to I C (each)	\ \ 3M/ finoley /	Fuiiteu/ D-
8.	-	d/Molex or equivalent			i ajitsa/ b-
		3M/ finolex			
		/Fujitsu/ D-			
8 a	10 meters	link/Legrand/Molex			В
l o a	TO meters	or equivalent			
		brand of repute			
		3M/ finolex			
8 b	20 meters	/Fujitsu/ D-			В
	20 11161613	link/Legrand/Molex			
	Ontical Fibe	er Patch Cord, SM, S	C to I C (each)	3M/ finaley /	Fuiiteu/ D-
9.		d/Molex or equivalent			i ujitsu/ D-
	miveogran	3M/ finolex			
		/Fujitsu/ D-			
9 a	10 meters	link/Legrand/Molex			В
l o a	10 11101010	or equivalent			
		brand of repute			
		3M/ finolex			
		/Fujitsu/ D-			
9 b	20 meters	link/Legrand/Molex			В
	20 11101013	or equivalent			
		brand of repute			
	Optical Fibe	er Patch Cord, SM, S	C to SC (each)	3M/ finolex /	Fuiitsu/ D-
10.	-	d/Molex or equivalent	• •		
		3M/ finolex	•		
		/Fujitsu/ D-			
10 a	10 meters	link/Legrand/Molex			
		or equivalent			
		brand of repute			
		3M/ finolex			
		/Fujitsu/ D-			
10 b	20 meters	link/Legrand/Molex			
		or equivalent			
		brand of repute			
44	Optical Fibe	er Patch Cord, SM, Lo	C to LC (each)	3M/ finolex /	Fujitsu/ D-
11.	-	d/Molex or equivalent	• • •		<u>-</u>
		3M/ finolex	•		
		/Fujitsu/ D-			
11 a	10 meters	link/Legrand/Molex			
		or equivalent			
		brand of repute			
		3M/ finolex			
		/Fujitsu/ D-			
11 b	20 meters	link/Legrand/Molex			
		or equivalent			
		brand of repute			
12.	Optical Fibe	er Patch Cord, MM,	OM-3+SC to	LC (each) 3	M/ finolex
12.		ink/Legrand/Molex or		` '	
	_	3M/ finolex		-	
12 a	10 meters	/Fujitsu/ D-			В
ĺ		link/Legrand/Molex			
		mind Logiania, molox			

		or equivalent			
		brand of repute 3M/ finolex			
12 b	20 meters	/Fujitsu/ D- link/Legrand/Molex			В
		or equivalent brand of repute			
13.		tion for UTP CAT6/0 warranty (Per site)		er cabling wit	h 15 years
	Site up to				
13 a	1000 Nodes(Per	As per actual			В
	site) Supply & Fix	│ xing of Metal MS(∣ Cable Tray/ ra	ceway with	covers for
14.		n ceiling / floor/ w hanging, T- Cros			
1-7.	cables etc, s	ize as follows with	required fitting		
	above (per ru 50 mm	ınning meter) as pe	r actual		
	Height x 100				_
14 a	mm width Thickness				В
	1.6mm				
	50 mm Height x 200				
14 b	mm width Thickness				В
	1.6mm				
	100 mm Height x 300				
14 c	mm width				В
	Thickness 1.6mm				
	Supply & Fix	ing of High Grade I	PVC cable tra	y/ race way w	ith covers
15.		g on ceiling / floor, r hanging, T, Cr			
	Branching o	of cables etc, size	as follows w	ith required	fitting kit
		for above (per runni	ng meter)	T	
	50 mm Height x 150				
15 a	mm width Thickness				В
	2.5 mm to 3				
	mm 100 mm				
451	Height x 100				
15 b	mm width 2.5 mm to 3				В
	mm 100 mm				
	Height x 300				
15 c	mm width 2.5 mm to 3				В
	mm				
16.	surface	Installation / Fixin	g of GI Pipe	undergroun	d and on
16 a	1 inch diameter				В
16 b	1.5 inch				В
	diameter				

17.	Supply and installation/ Fixing of 4 Inch HUME pipe underground (Per Meter)			В
18.	Fiber optics cable route marker (Proper marking should be there in the form of pipe as per the directions of the High Court.)			В
19.	cable pulling pit made of reinforced concrete and brick walls with removable covers			В
20.	LAN Survey	& Document Prepar	ation	
20 a	for up to 1000 network nodes, per node			В
20 b	for more than 1000 network nodes, per node			В
21.	Blower	(D-link / Eureka Forbes or repute brand)		В
22.	Four pair wire LAN Crimping Tool	D-link / Krone or repute brand		В
23.	LAN Punching Tool	D-link / Krone or repute brand		В
24.	LAN Tester	D-link / Krone or repute brand		В

Specification -"A"

S.No.	Item Description	OEM Make/Part No.	Proposed make/brand by the bidder	Technically Complied Yes/No
33.	8 port Network Switches (manageable) Specification- "A"	CISCO / Dell / HP / Juniper		
33 a	No. Of 10/100/1000 Mbps Base T Ports 8			
33 b	Support Entries In The MAC Table 8000			
33 c	Minimum Switching Capacity 8 Gbps			
33 d	Minimum Forwarding capacity 1.4 Mbps			
33 e	Should have QoS, Loop detection, Jumbo frame(9216),feature			
33 f	Operative temperature 0 to 40 degree C			
33 g	Should be under suitable housing as per certified organization.			
33 h	Onsite warranty			

Specification-"B".

34.	12 port Aggregation Switch Specification- "B".	CISCO / Dell / HP / Juniper	
34 a	"Switch OEM should		
	be in the Gartner's Leaders or Challengers		
	or visionary quadrant		
	for Wired and		
	Wireless LAN Access		
	Infrastructure or data		
	center networking		
	published in 2017 or later".		
34 b	12 port 10G SFP+ and 2		
0.5	or 4, 10G uplink ports		
	populated with SM fiber.		
34 c	Switch should have 32K		
	MAC and 4GB RAM.		
	Switch should have		
	Redundant power supply		
34 d	and multiple FANS. Switch should have Layer		
0.4	3 features RIP, OSPF,		
	BGP, VRRP, PBR from		
	day one.		
	Switch should have CLI,		
	TELNET, SNMPv3,		
	RMON capability		

Specification-"C".

35.	24 port Aggregation Switch Specification- "C".	CISCO / Dell / HP / Juniper	
35 a	"Switch OEM should	- Campo	
	be in the Gartner's		
	Leaders or Challengers		
	or visionary quadrant		
	for Wired and		
	Wireless LAN Access		
	Infrastructure or data		
	center networking		
	published in 2017 or		
	later".		
35 b	24 port 10G SFP+ and 2		
	x 40G uplink ports		
	populated with SM fiber.		
35 c	Switch should have 32K MAC and 4GB RAM.		
	Switch should have		
	Redundant power supply		
	and multiple FANS.		
35 d	Switch should have Layer		
	3 features RIP, OSPF, BGP, VRRP, PBR from		
	day one.		
	Switch should have CLI,		
	TELNET, SNMPv3,		
	RMON capability		

Specification -"D"

36.	*24 port Ethernet managed enterprise series switch with all accessories and Power over Ethernet (PoE)	CISCO / Dell / HP / Juniper	
36 a	Switch OEM should be in the Gartner's Leaders or Challengers or visionary quadrant for Wired and Wireless LAN Access Infrastructure or data center networking published in 2017 or later.		
36 b	Switch should be 1RU with minimum 24 nos. 10/100/1000 Base-T ports with PoE+ capability and minimum 370W of PoE Power and additional 4 nos. SFP+ uplinks ports		
36 c	SFP modules asked in S/N no. 56 should be from same OEM		
36 d	Switch should support (excluding uplinks) for minimum 56 Gbps of stacking bandwidth with dedicated		

	T	
	stacking ports and cables with minimum 8 switch in stack.	
	"Switch should have internal	
00	power supply. Should have	
36 e	internal redundant power	
	supply from day one."	
	Switch shall have minimum	
00.1	88 Gbps of switching fabric	
36 f	and 65 Mpps of forwarding	
	rate.	
	Shall have minimum 16 K	
36 g	MAC Addresses and 250	
	active Vlans.	
	Should support IEEE	
	Standards of Ethernet: IEEE	
36 h	802.1D, 802.1s, 802.1w,	
30 11	802.3az, 802.1x, 802.3ad, 802.3x, 802.1p, 802.1Q,	
	802.3, 802.3u, 802.3ab,	
	802.3z.	
	Shall have 802.1p class of	
	service, marking,	
36 i	classification, policing and	
	shaping. Should support strict	
	priority queuing.	
	Switch should support	
36 j	management features like SSHv2, SNMPv2c, SNMPv3,	
30 j	NTP, RADIUS and TACACS+	
	Switch should support port	
	security, DHCP snooping,	
36 k	Dynamic ARP inspection, IP	
	Source guard, BPDU Guard,	
	Spanning tree root guard.	
	Switch should support IPv6	
	Snooping, IPv6 RA Guard, IPv6 DHCP Guard, IPv6	
36 I	Neighbor Discovery	
	Inspection and IPv6 Source	
	Guard.	
	Should support 802.1x	
	authentication and	
36 m	accounting, IPv4 and IPv6	
	ACLs and Dynamic VLAN	
	assignment.	
	Switch must have support for	
36 n	L3 functionality like static routing, RIP, PIM, OSPF and	
	PBR from Day1	
	"Switch should support	
00	application visibility and	
36 o	traffic monitoring with	
	netFlow/sflow/ jflow entries."	
	Switch shall conform to UL	
	60950 or IEC 60950 or CSA	
36 p	60950 or EN 60950	
	Standards for Safety	
	requirements of Information	
	Technology Equipment. Switch shall conform to EN	
36 q	55022 Class A/B or CISPR22	
	OUULL DIASS FAD OF CIOF INZE	

	Class A/B or CE Class A/B or FCC Class A/B Standards for EMC (Electro Magnetic Compatibility) requirements.	
36 r	Switch should be tested and certified for EAL/NDPP or above under Common Criteria Certification.	
36 s	Switch should be IPv6 logo ready Certified/ IPv6 ready from Day 1.	

Specification -"E"

	*** · F.* · ·	01000 / 5 **	I	I
	*24 port Ethernet managed	CISCO / Dell		
37.	enterprise series switch	/ HP /		
	with all accessories.	Juniper		
	"Switch OEM should be			
	in the Gartner's Leaders or			
	Challengers or visionary			
37 a	quadrant for Wired and			
31 a	Wireless LAN Access			
	Infrastructure or data center			
	networking published in 2017			
	or later"			
	"Switch should be 1RU with			
	minimum 24 nos.			
37 b	10/100/1000 Base-T ports			
	and additional 4 nos. SFP+			
	uplinks ports".			
	SFP modules asked in S/N			
37 c	no. 56 should be from same			
	OEM			
	Switch should support			
	(excluding uplinks) for			
37 d	minimum 56 Gbps of stacking			
	bandwidth with dedicated			
	stacking ports and cables with minimum 8 switch in stack.			
	Switch should have internal			
37 e	power supply. Should			
37 e	support external/internal			
	redundant power supply.			
	Switch shall have minimum			
37 f	88 Gbps of switching fabric			
	and 65 Mpps of forwarding rate.			
	Shall have minimum 16 K			
37 g	MAC Addresses and 250			
- 3	active Vlans.			
	Should support IEEE			
	Standards of Ethernet: IEEE			
	802.1D, 802.1s, 802.1w,			
37 h	802.3az, 802.1x, 802.3ad,			
	802.3x, 802.1p, 802.1Q,			
	802.3, 802.3u, 802.3ab, 802.3z.			
	Shall have 802.1p class of			
07:	service, marking,			
37 i	classification, policing and			
	shaping. Should support strict			

	priority queuing.	
	Switch should support	
	management features like	
37 j	SSHv2, SNMPv2c, SNMPv3,	
	NTP, RADIUS and TACACS+	
	Switch should support port	
07.1	security, DHCP snooping,	
37 k	Dynamic ARP inspection, IP	
	Source guard, BPDU Guard,	
	Spanning tree root guard.	
	Switch should support IPv6	
	Snooping, IPv6 RA Guard,	
37 L	IPv6 DHCP Guard, IPv6	
	Neighbor Discovery	
	Inspection and IPv6 Source	
	Guard.	
	Should support 802.1x authentication and	
37 m	authentication and accounting, IPv4 and IPv6	
37 111	ACLs and Dynamic VLAN	
	1	
	assignment. Switch must have support for	
	L3 functionality like static	
37 n	routing, RIP, PIM, OSPF and	
	PBR from Day1	
	"Switch should support	
	application visibility and	
37 o	traffic monitoring with	
	netFlow/sflow/jflow entries"	
	Switch shall conform to UL	
	60950 or IEC 60950 or CSA	
	60950 or EN 60950	
37 p	Standards for Safety	
	requirements of Information	
	Technology Equipment.	
	Switch shall conform to EN	
	55022 Class A/B or CISPR22	
0.7	Class A/B or CE Class A/B or	
37 q	FCC Class A/B Standards for	
	EMC (Electro Magnetic	
	Compatibility) requirements.	
	Switch should be tested and	
27 -	certified for EAL/NDPP or	
37 r	above under Common Criteria	
	Certification.	
27.0	Switch should be IPv6 logo	
37 s	ready Certified.	
	Switch OEM should be in the	
	Gartner's Leaders or	
	Challengers or visionary	
37 t	quadrant for Wired and	
	Wireless LAN Access	
	Infrastructure published in	
	2017 or later	

Specification -"F"

	*24 port Ethernet managed	CISCO / Dell	
38.	enterprise series switch with all accessories.	/ HP /	
	"Switch OEM should be in	Juniper	
	the Gartner's Leaders or		
	Challengers or visionary		
	quadrant for Wired and		
38 a	Wireless LAN Access		
	Infrastructure or data center		
	networking published in 2017		
	or later"		
	"The switch should have		
	minimum 24 x 10/100/ 1000		
	Mbps Ethernet Ports and 2		
38 b	dual-purpose port		
	(10/100/1000 or SFP). Switch		
	should have fans or fan-less		
	design for proper cooling"		
38 c	SFP modules asked in S/N no.		
36 6	56 should be from same OEM		
20 4	At least 16 Gbps Forwarding		
38 d	bandwidth and 6 Mpps forwarding rate		
38 e	"DRAM : 1GB & Flash : 1GB"		
	Configurable up to 8000 MAC		
38 f	addresses.		
	IEEE 802.1Q VLAN		
	encapsulation. Upto 250		
	VLANs should be supported.		
38 g	Support for 4000 VLAN IDs. Centralized VLAN		
	Management. VLANs created		
	on the Core Switches should		
	be propagated automatically.		
00 h	IEEE 802.1d, 802.1s, 802.1w,		
38 h	802.3ad. Link Aggregation Protocol (LACP)		
	Spanning-tree feature to		
38 i	prevent other edge switches		
	becoming the root bridge.		
60:	IGMP snooping v3, Support for		
38 j	upto 250 IGMP Groups. IGMP		
	filtering. Support for Detection of		
	Unidirectional Links (in case of		
38 k	fiber cut) and to disable them		
	to avoid problems such as		
	spanning-tree loops.		
	The Switch should be able to		
	discover the neighboring device of the same vendor		
20.1	giving the details about the		
38 L	platform, IP Address, Link		
	connected through etc, thus		
	helping in troubleshooting		
	connectivity problems. Per-port broadcast, multicast,		
38 m	and storm control to prevent		
L	and the provone	<u> </u>	1

	foulty and stations from	
	faulty end stations from	
	degrading overall systems	
	performance.	
	Local Proxy Address	
	Resolution Protocol (ARP) to	
38 n	work in conjunction with	
0011	Private VLAN Edge to	
	minimize broadcasts and	
	maximize available bandwidth.	
	Multicast VLAN registration	
	(MVR) to continuously send	
	multicast streams in a	
38 o	multicast VLAN while isolating	
	the streams from subscriber	
	VLANs for bandwidth and	
	security reasons.	
	Support for RFC 1492 -	
	TACACS+, RFC 2463 - ICMP	
	IPv6, RFC 2373 - IPv6	
38 p	Aggregatable Addrs, RFC	
00 P	2461 - IPv6 Neighbor	
	Discovery and RFC 2462 -	
	IPv6 Autoconfiguration	
	Min 500 ACL entries should be	
38 q	supported.	
	Four egress queues per port to	
38 r	enable differentiated	
	management.	
	SNMP v1, v2c, and v3 and	
	Telnet interface support	
	delivers comprehensive in-	
38 s	band management, and a CLI-	
	based management console	
	provides detailed out-of-band	
	management.	
	Switch shall conform to EN	
38 t	55022 Class A/B or CISPR22	
	Class A/B or CE Class A/B or	
	FCC Class A/B Standards for	
	EMC (Electro Magnetic	
	Compatibility) requirements.	
	Reduction of Hazardous	
	Substances, CE Marking.	
	Judotanices, CE Marking.	

Specification -"G"

39.	*24 port Ethernet managed enterprise series switch with all accessories.	CISCO / Dell / HP / Juniper	
39 a	"Switch OEM should be in the Gartner's Leaders or Challengers or visionary quadrant for Wired and Wireless LAN Access Infrastructure or data center networking published in 2017 or later"		
39 b	"The switch should have minimum 24 x 10/100/1000 Mbps Ethernet IEEE 802.3af Ports and 2 dual-purpose port (10/100/1000 or SFP). Minimum 370W of		

lans for proper cooling. SFP modules asked in S/N At least 16 Gbps Forwarding bandwidth and 6 Mpps forwarding rate DRAM: 1GB & Flash: 1GB Ornligurable up to 8000 MAC addresses. IEEE 802.1Q VLAN encapsulation. Upto 250 VLANs should be supported. Support for 4000 VLAN IDs. Centralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w. 39 h 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for 10 Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor ging the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and multicast VLAN registration (MVR) to continuously send multicast VLAN while isolating the streams in a multicast vLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons.		Dol Dower Chould have	\neg
39 c OEM OEM At least 16 Gbps Forwarding bandwidth and 6 Mpps forwarding rate 39 e DRAM: 1GB & Flash: 1GB 39 f Ornarding rate 39 e DRAM: 1GB & Flash: 1GB 39 f Ocnfigurable up to 8000 MAC addresses. IEEE 802.1Q VLAN encapsulation. Upto 250 VLANs should be supported. Support for 4000 VLAN IDs. Contralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams for bandwidth and security reasons.		PoE Power. Should have fans for proper cooling"	
OEM At least 16 Gbps Forwarding bandwidth and 6 Mpps forwarding rate 39 e DRAM: 1GB & Flash: 1GB Configurable up to 8000 MAC addresses. IEEE 802.1Q VLAN encapsulation. Upto 250 VLANs should be supported. Support for 4000 VLAN IDs. Centralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent of there edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP Groups. IGMP Groups. IGMP Groups. IGMP Groups. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams in security reasons.	30 c		
39 d bandwidth and 6 Mpps forwarding rate 39 e DRAM: 1GB & Flash: 1GB 39 f Configurable up to 8000 MAC addresses. IEEE 802.10 VLAN encapsulation. Upto 250 VLANs should be supported. Support for 4000 VLAN IDs. Centralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of their cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize broadcasts and maximize broadcasts and minimize broadcasts and minimizes broadcasts and security reasons.	330	OEM	
forwarding rate 39 e DRAM : 1GB & Flash : 1GB 39 f Onfigurable up to 8000 MAC addresses. IEEE 802.1Q VLAN encapsulation. Upto 250 VLANs should be supported. Support for 4000 VLAN IDs. Centralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups, IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast vLAN registration (MVR) to continuously send multicast streams in a multicast vLAN shile isolating the streams from subscriber VLANs for bandwidth and security reasons.	30 Y		
Configurable up to 8000 MAC addresses. IEEE 802.1Q VLAN encapsulation. Upto 250 VLANs should be supported. Support for 4000 VLAN IDs. Centralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams in a multicast streams in a multicast streams from subscriber VLANs for bandwidth and security reasons.	39 u	• •	
addresses. IEEE 802.1Q VLAN encapsulation. Upto 250 VLANs should be supported. Support for 4000 VLAN IDs. Centralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 39 h 80.23ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons.	39 e		
encapsulation. Upto 250 VLANs should be supported. Support for 4000 VLAN IDs. Centralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 39 h Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support IGMP snooping v3, Support IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons.	39 f		
VLAN's should be supported. Support for 4000 VLAN IDs. Centralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 802.3d. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast VLAN shelle isolating the streams from subscriber VLANs for bandwidth and security reasons.		<u> </u>	
Centralized VLAN Management. VLANs created on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast vLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -		VLANs should be supported.	
on the Core Switches should be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 802.3m, 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support of upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams in a multicast streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -	39 g		
be propagated automatically. IEEE 802.1d, 802.1s, 802.1w, 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams in a multicast streams from subscriber VLANs for bandwidth and security reasons.			
39 h 802.3ad. Link Aggregation Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams in a multicast streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -			
Protocol (LACP) Spanning-tree feature to prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with work in conjunction with S9 n Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams in a multicast streams from subscriber VLANs for bandwidth and security reasons.	00.1	IEEE 802.1d, 802.1s, 802.1w,	
39 i prevent other edge switches becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast vLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -	39 h	33 3	
becoming the root bridge. IGMP snooping v3, Support for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast vLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -	30 :	, ,	
39 j for upto 250 IGMP Groups. IGMP filtering. Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons.	391		
Support for Detection of Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with 39 n Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons.	30 i		
Unidirectional Links (in case of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with 93 n Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast vLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons.	39]		
39 k of fiber cut) and to disable them to avoid problems such as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. 39 p Support for RFC 1492 -			
as spanning-tree loops. The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons.	39 k	of fiber cut) and to disable	
The Switch should be able to discover the neighboring device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast vLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. 39 p. Support for RFC 1492 -		•	
device of the same vendor giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast vLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. 39 p. Support for RFC 1492 -			
giving the details about the platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. 39 p. Support for RFC 1492 -			
platform, IP Address, Link connected through etc, thus helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast vLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -	30 1		
helping in troubleshooting connectivity problems. Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons.	39 L	1 .	
Per-port broadcast, multicast, and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast vLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -		,	
and storm control to prevent faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with 39 n Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -		connectivity problems.	=
faulty end stations from degrading overall systems performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -			
performance. Local Proxy Address Resolution Protocol (ARP) to work in conjunction with 39 n Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -	39 m	faulty end stations from	
Resolution Protocol (ARP) to work in conjunction with 39 n Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -		, ,	
work in conjunction with Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a 39 o multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -		Local Proxy Address	
39 n Private VLAN Edge to minimize broadcasts and maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -			
maximize available bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -	39 n	Private VLAN Edge to	
bandwidth. Multicast VLAN registration (MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -			
(MVR) to continuously send multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -		bandwidth.	
multicast streams in a multicast VLAN while isolating the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -		_	
the streams from subscriber VLANs for bandwidth and security reasons. Support for RFC 1492 -	00	multicast streams in a	
VLANs for bandwidth and security reasons. Support for RFC 1492 -	39 o	1	
39 p Support for RFC 1492 -		VLANs for bandwidth and	
39 N ''		i	\dashv
	39 p	· ·	

	IPv6, RFC 2373 - IPv6 Aggregatable Addrs, RFC	
	2461 - IPv6 Neighbor	
	Discovery and RFC 2462 -	
	IPv6 Auto configuration Min 500 ACL entries should	
39 q	be supported.	
	Rate limiting should be	
	provided based on source	
	and destination IP address,	
	source and destination MAC	
39 r	address, Layer 4 TCP and UDP information, or any	
	combination of these fields,	
	using QoS ACLs (IP ACLs or	
	MAC ACLs), class maps, and	
	policy maps.	
	SNMP v1, v2c, and v3 and	
	Telnet interface support	
	delivers comprehensive in-	
39 s	band management, and a	
	CLI-based management	
	console provides detailed out- of-band management.	
	Switch shall conform to EN	
39 t	55022 Class A/B or CISPR22	
	Class A/B or CE Class A/B or	
	FCC Class A/B Standards for	
	EMC (Electro Magnetic	
	Compatibility) requirements.	
	Reduction of Hazardous	
	Substances, CE Marking.	

Note:-

- All network switches to be compatible with the existing LAN infrastructure of the High Court and District Courts on IEEE standard protocols.
- All the quoted products make and model shall be finalized by the committee of the High Court.
- All quoted switches (*Except 8port switch*) should have minimum 1GB RAM and 1GB flash.
- 4. Switch should be tested and certified for EAL/NDPP or above under Common Criteria Certification.
- 5. Switch should be IPv6 ready / logo ready Certified.
- 6. The specifications mentioned in tender document are minimum and the vendor may quote higher specifications items.
- 7. The network switches should have proper fans for cooling or should have fanless design for proper cooling.
- 8. All the pages of the bids and Annexure's are to be sealed and signed by the authorized officers of the company / vendor.

- 9. The bidder has to quote only 01 product of single make / brand at a time and not multiple brands for same item.
- 10. The Original equipment manufacturer (OEM) may authorize more than one partner for participation in the bid.
- Back-to-Back support letter is to be submitted by OEM regarding support of the quoted products.
- 12. The Registrar General, High Court of Madhya Pradesh has full rights to accept or reject any bid, without assigning any reason.
- 13. All Prospective bidders are requested to submit the bid with all relevant documents and product brochures / catalogues.
- 14. All the managed switches should be from same OEM.

8.2 Structured Cabling

- 8.2.1 The Bidder is required to install and commission the structured cabling involving CAT 6 Cables, Surface Mount I/Os, Jack Panel, PVC conduit / casing / capping with accessories, any other required components such as labels, ferrules etc., and all associated civil works in accordance with the following guidelines:-
 - Carrying out of the required surveys prior to installation work is the responsibility of the Successful Bidder, if deemed necessary.
 - ii. The cabling job should be carried out under the supervision of Network Certified Engineers.
 - iii. All the wiring should be fully concealed inside the conduit /casing and no cable (except patch cords) should be visible to the naked eye.
 - iv. The cabling shall be properly labeled and ferruled so as to facilitate easy identification and maintenance. The labeling and ferruling shall be documented.
 - v. All civil work like cutting, chasing, drilling, etc. shall be finished to ensure smooth leveled surfaces matching the existing aesthetics of the office to the extent possible.
 - vi. All waste material shall be properly disposed off from the Registrar General, High Court of Madhya Pradesh premises in an environment friendly manner and complaint to applicable civil /municipal guidelines.

- 8.2.2 Testing, in conformance to measurement procedures and test parameters for CAT 6 installation as defined in TIA/EIA-568-B standards, of each node using a penta scanner. The **certified test results** are to be submitted to High Court of M.P., Jabalpur in hard copy.
- 8.2.3 Certification of each site for minimum <u>15 years performance</u> warranty based on the above test results from the manufacturer of the structured network cabling components.
- 8.2.4 The cabling components and the system (cables, I/Os, Patch Cords and Jack Panel) shall.
 - (i) IEEE 802.3 compliant
 - (ii) Conform to the TIA/EIA 568 standard
 - (iii) UL listed
- 8.2.5 The PVC conduit / casing / capping / all accessories and other required components including labels, ferrules, and any other proposed components shall **be ISI /ISO certified**.
- 8.2.6 The Bidder shall provide the details (technical specifications, dimensions, brochures, make, model, photo catalogues) and conformance to standards mentioned in the tender document.

9. The bidder has to adopt following guidelines for Cabling & Networking:-

9.1 Twisted Pair cable guidelines:-

CONDITION	< 2KVA	2-5KVA	>5KVA
Unshielded power lines or electrica	5 inches or	12 inches	24 inches
equipment in the proximity to open or non-	·12.7 cm	or 30.5 cm	or 61 cm
metal pathways.			
Unshielded power lines or electrica	2.5 inches	6 inches or	12 inches
equipment in the proximity to grounded meta	or 6.4 cm	15.2 cm	or 30.5 cm
conduit pathway.			
Power lines enclosed in a grounded meta		6 inches or	12 inches
conduit (equivalent shielding) in the proximity	1	15.2 cm	or 30.5 cm
to grounded metal conduit pathway.			
Fluorescent lighting.	12 inches or 30.5 cm		
Transformers & electric motors.	40 inches or	1.02 meter	

9.2 Minimum bending radius for a cable:-

a. According to EIA/TIA SP-2840A the minimum-bending radius for UTP is 4 x cable outside diameter, about 1 inch. For multi-pair cable the minimum-bending radius is 10 x outside diameter.

- b. For fiber optic cables not in tension, the minimum bend radius is 10 x diameter; cables loaded in tension may not be bent at less than 20 x diameter. SP-2840A states that no fiber optic will be bent on a radius less than 3.0 cm (1.18 inches).
- c. Minimum for pulling during installation is 8 x cable diameter; minimum installed radius is 6 x cable diameter for riser cable. 4 x cable diameter for horizontal cable.

9.3 Do's and Don'ts for the Bidder:-

Do's	Don'ts
Use connecting hardware that	Do not use connecting hardware that is of
is compatible with the installed	a lower category than the cable being
cable.	used.
Terminate each horizontal cable on	Do not tap a new line from the middle of
a dedicated telecommunications	another cable (called bridge taps), as it
outlet.	picks up more noise. Do not leave cables
	un-terminated.
Locate the main cross-connect near	Do not locate cross-connects where cable
the center of the building to limit cable	distance will exceed the maximum allowed
distances.	distance.
Maintain the twist of horizontal and	Do not leave any wire pairs untwisted
backbone cable pairs up to the point of	(Keep the twist until the closest possible
terminations.	places to the terminations).
Tie and dress horizontal cables neatly	Do not over-tighten cables ties. Never
and with a minimum bend radius of 4	use staples or make sharp bends with
times the cable diameter.	cables.
Place cabling at a sufficient distance	Do not place cable near equipment that
from equipment.	may generate high levels of EMI (i.e.,
	electricity wire (power line) and fluorescent
	light).

For running cable the bidder has to follow following rules:-

- A. Always use more cable than you need. Leave plenty of slack.
- B. Test every part of a network as the time of installation. Even if it is brand new, it may have problems that will be difficult to isolate later.
- C. Stay at least 3 feet away from fluorescent light boxes and other sources of electrical interference.
- D. If it is necessary to run cable across the floor, cover the cable with cable protectors.
- E. Label both ends of each cable.
- F. Use cable ties (not tape) to keep cables in the same location together.
- G. The conduit or casing should not be filled completely with the cables. There should be room for future expansion.

9.4 UTP Cabling Installation:-

- 9.4.1 To avoid stretching, pulling tension should not exceed 110N or (25 lb *f*) for 4-pair cables.
- 9.4.2 Installed bend radii shall not exceed: 4 times the cable diameter for horizontal UTP cables. -10 times the cable diameter for multi-pair backbone UTP cables.
- 9.4.3 Avoid cable stress, as caused by:- cable twist during pulling or installation tension in suspended cable runs tightly clinched cable ties or staples tight bend radii.
- 9.4.4 Horizontal cables should be used with connecting hardware and patch cords (or jumpers) of the same performance category or higher.
- 9.4.5 Important Note: Installed UTP cabling shall be classified by the least performing component in the link.

9.5 General Guidelines to the Contractor / Bidder:-

- 9.5.1 Tagging each network terminal for easy identification by using Numeric Tags.
- 9.5.2 Unique tag code for uplink so that it is easily identified e.g. Numeric Tag 00.
- 9.5.3 Proper Termination of Fiber Optics Cable if any use or to be used.
- 9.5.4 Stands for switches should be provided so that the switch is rack mountable.
- 9.5.5 Port of the Patch Panel should be numbered so that the node can be tracked with Numeric Tag.
- 9.5.6 I/O port should be provided and numbered accordingly.

9.6 Documentation to be submitted by the contractor:-

- 9.6.1 Details Descriptive documentation of the Structural Cabling.
- 9.6.2 Test Report of the Network Cable with a comparison of test parameter with the specification parameter and variation.

- 9.6.3 Evaluation Report of the Built IT Infrastructure.
- 9.6.4 Drawings showing the location of cable runs, (preferably with individual cable lengths marked for any legacy thin Ethernet runs).
- 9.6.5 Size and occupancy of any existing cable ducts or conduits, which are available for use when expanding the network.
- 9.6.6 Details of the capacity and type of cabling and connectors used.
- 9.6.7 Details of type of connectors or sockets at either end of each cable
- 9.6.8 Records of the designation and location of outlets.
- 9.6.9 Any certification carried out on the cabling (e.g. Cat 6 test results).
- 9.6.10 Diagrams showing the relationships of various workstations, file servers, printers and other devices on the network to one another.
- 8.6.11 Diagrams showing how any hubs, bridges, switches or routers are used to connect the network (may be shown on a network management system).
- 9.6.12 Records of software licenses and versions of software installed.
- 9.6.13 Configurations of Network Interface Cards.

9.7 Site Certification of the Infrastructure:-

Most important part of any infrastructure is its cabling structure on which the infrastructure would be running. There are standards to be followed by the contractor so that performance and quality assurance is guaranteed. This guarantee can also be termed as Site Certification.

There following rules to be followed by the contractor for Site Certification.

9.7.1 Site Certification is provided by the manufacturer against infrastructure build by the System Integrator using the standards.

- 9.7.2 Standards are typical methods that been have tested by the manufacturer according to the BISCI Standard for its quality performance.
- 9.7.3 The part products used in Structured cabling all should be of one manufacturer of certain specification throughout to have minimum tolerance.
- 9.7.4 Cable Selection should be such considering all future aspects.
- 9.7.5 Cable Selected should be used with appropriate connectors.
- 9.7.6 All cables should be concealed according to Pathways and Spaces Standards.
- 9.7.7 Test reports with the details of the loss of signal in terms of crosstalk and due to other factors affecting it.

Annexure-I TECHNO-COMMERCIAL BID

S.No.	Description	Indicate page
	2000.15.1011	number
		where the
		documents
		are enclosed
1.	Name, address & telephone number of the Bidder.	are energed
2.	Name, designation, address & telephone number of	
	authorized person	
3.	Please specify as to whether Tenderer is sole	
	Proprietor/Partnership Firm/Private or Limited	
	Company.	
4.	Name, address & telephone number of	
	Directors/Partners, Fax No., e-mail address.	
5.	Copy of PAN Card issued by Income Tax	
	Department and Copy of previous 3 Financial	
	Year's Income Tax Return 2016-17, 2017-18 and	
	2018-19. The average turnover of the bidder during	
	last three financial years should be minimum	
	Rupees 02 crore.	
6.	Copy of Valid GST registration details	
7.	Copy of valid ISO certification of the bidder in the	
	field of Local Area Networking (LAN) and / or Wide	
	Area Networking (WAN) work	
8.	Valid ISO / ISI Certificate of the products to be	
	supplied and installed (Please attach copy)	
9.	List of company service centers in M.P.	
10.	Latest GST Return.	
11.	Experience Certificate / details for last <u>5 years</u>	
	regarding installation of Local Area Networking.	
12.	Authorization letter / MAF from OEM's to sale the	
	product in order to have back-to-back warranty and	
	support.	
13.	Details of Bid Security/Earnest Money Deposit:	
	a) Amount: 4,00,000/-	
	b) Demand Draft/Pay	
	Order/Banker/Cheque No.:	
	c) Date of issue:	
	d) Name of issuing Bank:	
14.	Details of online tender fees	
15.	Furnish the list of Service Engineers and	
	Operators to be deputed for installation of Network	
	at High Court of Madhya Pradesh and Subordinate	
	Courts in the State of Madhya Pradesh.	

Declaration by the Bidder:

This is to certify that I/We before signing this tender have read and fully understood all the terms and conditions contained in the tender document and undertake myself/ourselves to strictly abide by them.

Signature of the Tenderer with Seal

Note:- Please indicate the page numbers where documents are attached. The entire Tender documents should be serially page numbered including enclosures.

It is certified that the particulars given above are true to the best of my/our knowledge/behalf and I/We have read terms/conditions and duties/responsibilities of the Technical Staff to be deputed for the purpose and have also understood the same and to hereby undertake to abide by the same without any reservations on any grounds whatsoever. In case of any breach of the said conditions. I/We shall be responsible for the consequences arising out of such situation(s).

Name & Signature of the
Authorized Signatory of the Agency
(with Seal of the Agency affixed)

Date:	
Place:	

Annexure-II PRICE BID

Detail Break up of Cost*
Name of the Bidder:
Price Bid Part –"A"

S.No.	Item Description	OEM Make/Part No.	Proposed make/brand quote by the bidder	Unit Rate Per Item / per work/ job	GST TAX (%)	Any other duty/ levy	Unit Price in Rupees (all inclusive)
1	2	3	4	5	6	7	8=7+6+5
1.	UTP CAT 6 cable (Box of 305 m)	D-link/ Legrand /Molex or equivalent brand of repute					
2.	24 port Patch Panel CAT 6 (each)	D-link/ Legrand/ Molex or equivalent brand of repute					
3.		tlet CAT 6 (faceplate			box (e	ach co	mplete set)
J.	D-link/ Legrand	/Molex or equivalent I	prand of reput	е	Г	Г	
3 a	1-port	D-link/ Legrand/ Molex or equivalent brand of repute					
3 b	2-port	D-link/ Legrand/ Molex or equivalent brand of repute					
3 c	4-port	D-link/Legrand/ Molex or equivalent brand of repute					
4.	Patch Cords CA or equivalent be	AT 6 (each) At least in	2 colour as p	oer orde	er) D-li	nk/Leg	rand/Molex
4 a	1 Meter	D-link/Legrand/ Molex or equivalent brand of repute					
4 b	2 Meter	D-link/Legrand/ Molex or equivalent brand of repute					
5.		NENTS- Fiber Optic r Meter) 3M/ finolex					
5 a	6 core	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute					
5 b	12 core	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute					
6.		tdoor armoured cabl Legrand/Molex or equ				Meter) 3	3M/ finolex
6 a	6 core	3M/ finolex /Fujitsu/ D-link/Legrand/ Molexor equivalent brand of repute		•			
6 b	12 core	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex					

7.		Connector SC Type, Epoxyless (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute
7 a	SM	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute
8.		Connectors LC Type, Epoxyless (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute
8 a	SM	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute
9.	Optical Fiber link/Legrand/M	pigtail SC Type, 1 meter (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute
9 a	SM	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute
10.	Optical Fiber link/Legrand/M	pigtail LC Type, 1 meter (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute
10 a	SM	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute
11.		Patch Cord, MM SC to SC (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute
11 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute
12.		Patch Cord, MM, SC to LC (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute
12 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute
13.		Patch Cord, SM, SC to LC (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute.
13 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute
14.		Patch Cord, SM, SC to SC (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute.
14 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute
15.	_	Patch Cord, SM, LC to LC (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute.
15 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute
16.		Patch Cord, MM, OM-3+SC to LC (each) 3M/ finolex /Fujitsu/ Dolex or equivalent brand of repute
16 a	3 meters	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute

17.		/all mount enclosure ach) 3M/ finolex /Fujit				
17 a	LIU WITH SC MM COUPLER	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex				
17 b	LIU WITH SC SM COUPLER	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute				
17 c	LIU WITH LC MM COUPLER	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute				
17 d	LIU WITH LC SM COUPLER	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute				
18.		J/ 2U drawer style 19 accessories (each) 3 d of repute				
18 a	LIU WITH SC MM COUPLER	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute				
18 b	LIU WITH SC SM COUPLER	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute				
18 c	LIU WITH LC MM COUPLER	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute				
18 d	LIU WITH LC SM COUPLER	3M/ finolex /Fujitsu/ D-link/Legrand/ Molex or equivalent brand of repute				
19.	Installation & 7 Cabling	ermination, Docume	ntation & Site	Certification	of UTP and File	ber
19 a	In-building laying of UTP CAT 6A / CAT 6 Cable (Per Meter)	As per actual				
19 b	Installation & Termination or Information outlets (including termination of CAT 6/ CAT 6A Cable on I/O	As per actual				
19 c	Installation & Termination of UTP Cables on Patch Panel CAT 6/ CAT 6A with wire manager	As per actual				
19 d	Performance testing of the laid UTP CAT	As per actual				

	6/ CAT 6 A (Penta Scanner reports & documentation) (Per Node)							
20.		on for UTP CAT6/ arranty (Per site) As p			er cablinç	g with	15	years
20 a	Site up to 100 Nodes (Per site)	As per actual						
20 b	Site up to 500 Nodes (Per site)	As per actual						
21.	Supply & fixing	of ISI/ISO marked PV	C duct of	Size (P	er Meter) l	SI / ISO	(OE	M)
21 a	15 x 15 mm	ISI / ISO (OEM)						
21 b	30 x 25 mm	ISI / ISO (OEM)						
21 c	40 x 25 mm	ISI / ISO (OEM)						
22.	Supply and fixing	ng of PVC Conduit of	OD Size (Per Met	er) ISI / ISC	O (OEM))	
22 a	20 mm	ISI / ISO (OEM)						
22 b	32 mm	ISI / ISO (OEM)						
22 c	40 mm	ISI / ISO (OEM)						
23.	Removal of Old UTP/ Fiber / coaxial RS 232/telephone cables (per Meter)							
24.	In building laying of fiber in duct/ conduit							
	(per meter)							
25.		of fiber cable (per Me	ter)	,			1	
25 a	Excavation and resurfacing of the Soft soil (depth 1 meter)							
25 b	Excavation and resurfacing of the concreter (depth 1 meter)							
25 c	Overhead or through pole							
26.	Supply and Installation / Fixing of 2" (Inches) diameter HDPE PVC Jacket Underground or on surface (Per Meter)	Reputed Make						
27.	SC/LC connector termination on fiber optic cable							

	Fusion/						
28.	Mechanical						
	splicing						
29.	Supply and installation of						
29.	buffer tubing kit						
	Performance						
	testing of laid						
	fiber Öptic						
	cable for						
	continuity						
20	length & DB						
30.	loss as per EIA/TIA - 455-						
	60 document						
	for FO test						
	procedures &						
	documentation						
	of the results.						
31.		mounting Racks	T	T		Т	
	19" Rack, wall	Rittal/D-link,Valrack					
	Mount 530 mm depth, 9 U	or equivalent brand of repute					
	Height,	or repute					
	(lockable) with						
31 a	àll						
Sia	accessories(At						
	least 2 cooling						
	fan,1 cable						
	manager, 15A 6port spike						
	guard)						
	19" Rack, wall	Rittal/D-link,Valrack					
	Mount 530 mm	or equivalent brand					
31 b	depth, 12 U	of repute					
	Height, (lockable) with						
	all accessories						
	19" Rack, wall	Rittal/D-link,Valrack					
	Mount 800 mm	or equivalent brand					
	depth, 24 U	of repute					
	Height,						
	(lockable) with all						
31 c	accessories(At						
	least 2 cooling						
	fan,1 cable						
	manager, 15A						
	6port spike						
	guard) 19" Rack, wall	Rittal/D-link,Valrack					
	Mount 1000	or equivalent brand					
	mm depth, 32	of repute					
	U Height,	'					
	(lockable) with						
31 d	all accessories						
	(At least 2						
	cooling fan,1 cable manager,						
	15A 6port						
	spike guard)						
	<u>, i 3/</u>	1	ı	<u>I</u>	<u> </u>	<u> </u>	1

31 e	19" Rack, wall Mount 1000 mm depth, 42 U Height, (lockable) with all accessories (Atleast 2 cooling fan,1 cable manager, 15A 6port spike guard)	Rittal/D-link,Valrack or equivalent brand of repute			
32.	for up to 100	Document Preparation) 		
32 a	network nodes, per node				
32 b	for up to 500 network nodes, per node				
33.	8 port Network Switches (manageable) Specification- "A".	CISCO / Dell / HP / Juniper			
34.	12 port Aggregation Switch Specification - "B".	CISCO / Dell / HP / Juniper			
35.	24 port Aggregation Switch Specification- "C".	CISCO / Dell / HP / Juniper			
36.	24 port Ethernet managed enterprise series switch with all accessories and Power over Ethernet (PoE) Specification- "D".	CISCO / Dell / HP / Juniper			
37.	24 port Ethernet managed enterprise series switch with all accessories. (Specification- "E".)	CISCO / Dell / HP / Juniper			
38.	24 port Ethernet managed enterprise series switch with all accessories. (Specification- "F".)	CISCO / Dell / HP / Juniper			

	1 - 1	Г	1		1
39.	24 port Ethernet managed enterprise series switch with all accessories. (Specification- "G".)	CISCO / Dell / HP / Juniper			
40.	Dual Band Mesh WiFi router,2 number of gigabit Ethernet ports, should be expandable with smart roaming feature	D-link/ CISCO / Netgear/Linksys/Dell / HP / Juniper			
41.	*SFP modules of SM Should support both SM and MM fiber at minimum 1 GBPS. Should be same OEM as item no. 34 to 39	CISCO / Dell / HP / Juniper			
42.	Media convertor SM (Should support 10/100/1000 Ethernet to 10/100/1000 fiber Onsite support)	Reputed make			
43.	Media convertor MM (Should support 10/100/1000 Ethernet to 10/100/1000 fiber Onsite support).	Reputed make			
44.	Stacking module with stacking cable. Should be same OEM as item no. 34 to 39				
45.	10G SFP module (should support single or multi mode) should be same OEM as item no. 34 to				

	39					
46.	40G SFP module (single mode) should be same OEM as item no. 34 to 39					
47.	40G SFP module (multi mode) should be same OEM as item no. 34 to 39					
48.	UTP CAT 6A cable (Box of 305 m)	D-link/ Legrand/Molex or equivalent brand of repute				
49.		AT 6A (each) at leas alent brand of repute	as pei	orde	r) D-lin	k/ Legrand
49 a	3 Meter	D- link/Legrand/Molex or equivalent brand of repute				
49 b	7 Meter	D- link/Legrand/Molex or equivalent brand of repute				
49 c	10 Meter	D- link/Legrand/Molex or equivalent brand				

Annexure-II PRICE BID

Detail Break up of Cost*
Name of the Bidder:
Price Bid Part –"B"

			Γ		1	1	
S.No.	Item Description	OEM Make/Part No.	Proposed make/brand quote by the bidder	Unit rate per item / per work / job	GST Tax (%)	Any other duty / levy	Unit Price in rupees (all inclusive)
1	2	3	4	5	6	7	8=7+6+5
1.	Patch Cords	CAT 6 (each) At leas	st in 2 colour	as per	order/i	require	
•••	i atom corac	D-		<u>uo po:</u>		Gquii oi	
1 a	5 Meter	link/Legrand/Molex or equivalent brand of repute					
2.		Connector SC Typ Molex or equivalent			3M/ f	inolex /	Fujitsu/ D-
2 a	MM	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute					
3.		Connectors LC Ty Molex or equivalent) 3M/ f	inolex I	/Fujitsu/ D-
3 a	MM	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute					
4.		r pigtail SC Type /Molex or equivalent			M/ fir	olex /	Fujitsu/ D-
4 a	MM	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute					
_	Optical Fibe	r pigtail LC Type	. 1 meter (e	ach) 3	M/ fir	nolex /	Fuiitsu/ D-
5.		Molex or equivalent				'	.,
5 a	MM	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute					
6.	Optical Fibe	r Patch Cord, MM	SC to SC (each)	3M/ fi	nolex /	Fujitsu/ D-
U.		Molex or equivalent					
6 a	10 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute					
6 b	20 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute					
7.	-	Patch Cord, SM, State the time of main	•	-		-	

/Fujitsu/ D-link/Legrand/Molex or equivalent brand of repute								
7 a	3 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent						
7 b	10 meters	brand of repute 3M/ finolex /Fujitsu/ D- link/Legrand/Molex						
		or equivalent brand of repute 3M/ finolex						
7 c	20 meters	/Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute						
8.		r Patch Cord, MM,			3 M/ fi	inolex	/Fujitsu/	D-
0.	link/Legrand	/Molex or equivalent	t brand of rep	ute	T			
8 a	10 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute						
8 b	20 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex						
9.		r Patch Cord, SM,			3M/ fi	inolex	/Fujitsu/	D-
	link/Legrand	/Molex or equivalent 3M/ finolex	brand of rep	ute				
9 a	10 meters	/Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute						
9 b	20 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute						
10.		r Patch Cord, SM,			3 M / fi	inolex	/Fujitsu/	D-
	link/Legrand	/Molex or equivalent 3M/ finolex	t brand of rep	ute				
10 a	10 meters	/Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute						
10 b	20 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute						
11.		er Patch Cord, SM,	•	-	3M/ fi	inolex	/Fujitsu/	D-
	iink/Legrand	/Molex or equivalent 3M/ finolex	c prand of rep	ute 				
11 a	10 meters	/Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute						
11 b	20 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute						

12.	Optical Fiber Patch Cord, MM, OM-3+SC to LC (each) 3M/ finolex /Fujitsu/ D-link/Legrand/Molex or equivalent brand of repute						
12 a	10 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute					
12 b	20 meters	3M/ finolex /Fujitsu/ D- link/Legrand/Molex or equivalent brand of repute					
13.		ation for UTP CAT warranty (Per site)		Fiber	cablir	ng with	15 years
13 a	Site up to 1000 Nodes(Per site)	As per actual					
14.	Supply & Fixing of Metal MS Cable Tray/ raceway with covers for mounting						
14 a	50 mm Height x 100 mm width Thickness 1.6mm	Reputed Make	V				
14 b	50 mm Height x 200 mm width Thickness 1.6mm	Reputed Make					
14 c	100 mm Height x 300 mm width Thickness 1.6mm	Reputed Make					
15.	Supply & Fixing of High Grade PVC cable tray/ race way with covers for mounting on ceiling / floor/ wall, with all connecting fittings & sections for hanging, T, Cross, L, vertical up/down routing. Branching of cables etc, size as follows with required fitting kit accessories for above (per running meter)						
15 a	50 mm Height x 150 mm width Thickness 2.5 mm to 3 mm	Reputed Make					
15 b	100 mm Height x 100 mm width 2.5 mm to 3 mm	Reputed Make					
15 c	100 mm Height x 300 mm width 2.5 mm to 3 mm	Reputed Make					
16.		nstallation / Fixing o	of GI Pipe und	ergroui	nd and	on sur	face
16 a	1 inch	Reputed Make					

	diameter					
16 b	1.5 inch	D t. IM-I.				
	diameter	Reputed Make				
	Supply and					
	installation/					
	Fixing of 4					
17.	Inch HUME	Reputed Make				
	pipe	•				
	underground					
	(Per Meter)					
	Fiber optics					
	cable route					
	marker					
	(Proper					
	marking					
	should be					
18.	there in the	Reputed Make				
	form of					
	pipe as per					
	the					
	directions					
	of the High					
	Court.)					
	cable pulling					
	pit made of reinforced					
	concrete					
19.	and brick	Reputed Make				
	walls with					
	removable					
	covers					
20.		& Document Prepar	ation			L
	for up to					
	1000					
20 a	network					
	nodes, per					
	node					
	for more					
	than 1000					
20 b	network					
	nodes, per					
	node	(D.1) (E.)				
21.	Diame	(D-link / Eureka				
	Blower	Forbes or repute				
	Four poir	brand)				
22.	Four pair wire LAN	D link / Krong or				
	Crimping	D-link / Krone or				
	Tool	repute brand				
	LAN					
23.	Punching	D-link / Krone or				
	Tool	repute brand				
		D-link / Krone or				
24.	LAN Tester	repute brand				
I	<u>l</u>	1 . 3 3 3 3 3 3	<u> </u>	1	l	<u>I</u>

Total Bid Price (Rs)
In words
Signature of Bidder with seal
Name
Business address

Tel. No. & Mobile No	
Email :	
Place:	
Date:	

Note:-

- 1. The criteria for selection of bidder will be based on table-"A" of the financial sheet. All the line items rates are to be filled by the prospective bidders.
- 2. Not mentioning the rates in the financial bid / commercial bid of any of the line item may lead to disqualification of the bid.
- 3. The quantities mentioned above are indicative only. The Registrar General reserves the right to change the quantities and the configuration of items mentioned above without assigning any reason thereof.
- 4. The payment to the vendor shall be made as per actual use of above items for the Installation of Local Area Networking and other related work.
- 5. All prospective bidders are requested to submit the bid and if there is any deviation in the specification, please mention the same in the deviation statement sheet.
- 6. The shortlisted vendor has to complete the LAN work within the fixed time frame.
- 7. The payment shall be made to successful bidder, only after submitting requisite document to the High Court as per the tender document.
- 8. The network switches to be compatible with the existing LAN infrastructure of the High Court and District Courts.
- 9. All the quoted products make and model shall be finalized by the committee of the High Court.

CERTIFICATES

WE CERTIFY THAT:

- 1. We will not <u>LEAK / DISCLOSE</u> any information of High Court of Madhya Pradesh to any other institutions/organizations, bodies and also in the market on the rates less than the prices quoted by us to the High Court.
- 2. The rate of <u>TAXES / DUTIES</u> mentioned in the tender is in accordance with the provisions of the rules in all respects and the same is payable to the Government Authorities.
- 3. The material / items offered shall be of the <u>best quality</u> strictly in accordance with the specifications and particulars as detailed in the tender.
- 4. The information furnished by us in the tender are true and correct to the best of our knowledge and belief.
- 5. We have read and understood the rules, regulations, terms and conditions of tender as applicable from time to time and agree to abide by them.

Authorized Signatory

(Seal of the Company)